



Water Cooled 50KW Diesel Generator Cummins Genset 50HZ / 60HZ

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DELLENT
- Certification: CE/ISO9001
- Model Number: DE-C22~C66
- Minimum Order Quantity: 1 PC
- Price: bargain face-to-face
- Packaging Details: PLASTIC WRAP OR PLYWOOD CASE
- Delivery Time: 20-30 DAYS
- Payment Terms: L/C, T/T
- Supply Ability: 1 MONTH 600PCS



Product Specification

- Name: 50KW Diesel Generator Cummins
- Engine Brand: Cummins
- Cooling Method: Water-Cooling System
- Fuel Type: Diesel
- Rated Frequency: 50HZ/60HZ
- Speed: 1500RPM/1800RPM
- Warranty: 12 Months/1000 Hours
- Highlight: **50KW Diesel Generator Cummins, 50kw Cummins Generator, Cummins Genset**

for more products please visit us on dellentpower.com

CE Cummins Diesel Generator about 50kW.

Our Cummins diesel generators are known for their durability, fuel efficiency, and low maintenance requirements. With Cummins engines at their core, these generators offer reliable power output that can be trusted for a range of applications. From backup power for homes and businesses to powering construction sites and events, our Cummins diesel generators deliver the power you need when you need it.

We also prioritize ease of use and maintenance for our customers. Our generators are designed with a user-friendly interface and easy access to key components for maintenance and repairs. Regular maintenance is essential for the longevity and optimal performance of your generator, and our team can provide support and guidance for creating a maintenance schedule that suits your specific needs.

. PRODUCT

50-60 Hz TECHNICAL DATA											
Model	Rated Power (kW)	Rated Power (kVA)	Rated Voltage (V)	Rated Frequency (Hz)	Rated Current (A)	Rated Speed (rpm)	Rated Efficiency (%)	Rated Fuel Consumption (L/h)	Rated Oil Consumption (L/h)	Rated Noise (dB)	Rated Weight (kg)
DC-020	20	22.3	230	50	48.4	1500	85	10.5	0.5	65	150
DC-025	25	27.5	230	50	58.8	1500	85	12.5	0.5	65	150
DC-030	30	33	230	50	69.3	1500	85	14.5	0.5	65	150
DC-035	35	38.3	230	50	79.8	1500	85	16.5	0.5	65	150
DC-040	40	44	230	50	90.3	1500	85	18.5	0.5	65	150
DC-045	45	49.5	230	50	100.8	1500	85	20.5	0.5	65	150
DC-050	50	55	230	50	111.3	1500	85	22.5	0.5	65	150
DC-055	55	60.5	230	50	121.8	1500	85	24.5	0.5	65	150
DC-060	60	66	230	50	132.3	1500	85	26.5	0.5	65	150
DC-065	65	71.5	230	50	142.8	1500	85	28.5	0.5	65	150
DC-070	70	77	230	50	153.3	1500	85	30.5	0.5	65	150
DC-075	75	82.5	230	50	163.8	1500	85	32.5	0.5	65	150
DC-080	80	88	230	50	174.3	1500	85	34.5	0.5	65	150
DC-085	85	93.5	230	50	184.8	1500	85	36.5	0.5	65	150
DC-090	90	99	230	50	195.3	1500	85	38.5	0.5	65	150
DC-095	95	104.5	230	50	205.8	1500	85	40.5	0.5	65	150
DC-100	100	110	230	50	216.3	1500	85	42.5	0.5	65	150
DC-105	105	115.5	230	50	226.8	1500	85	44.5	0.5	65	150
DC-110	110	121	230	50	237.3	1500	85	46.5	0.5	65	150
DC-115	115	126.5	230	50	247.8	1500	85	48.5	0.5	65	150
DC-120	120	132	230	50	258.3	1500	85	50.5	0.5	65	150
DC-125	125	137.5	230	50	268.8	1500	85	52.5	0.5	65	150
DC-130	130	143	230	50	279.3	1500	85	54.5	0.5	65	150
DC-135	135	148.5	230	50	289.8	1500	85	56.5	0.5	65	150
DC-140	140	154	230	50	300.3	1500	85	58.5	0.5	65	150
DC-145	145	159.5	230	50	310.8	1500	85	60.5	0.5	65	150
DC-150	150	165	230	50	321.3	1500	85	62.5	0.5	65	150
DC-155	155	170.5	230	50	331.8	1500	85	64.5	0.5	65	150
DC-160	160	176	230	50	342.3	1500	85	66.5	0.5	65	150
DC-165	165	181.5	230	50	352.8	1500	85	68.5	0.5	65	150
DC-170	170	187	230	50	363.3	1500	85	70.5	0.5	65	150
DC-175	175	192.5	230	50	373.8	1500	85	72.5	0.5	65	150
DC-180	180	198	230	50	384.3	1500	85	74.5	0.5	65	150
DC-185	185	203.5	230	50	394.8	1500	85	76.5	0.5	65	150
DC-190	190	209	230	50	405.3	1500	85	78.5	0.5	65	150
DC-195	195	214.5	230	50	415.8	1500	85	80.5	0.5	65	150
DC-200	200	220	230	50	426.3	1500	85	82.5	0.5	65	150
DC-205	205	225.5	230	50	436.8	1500	85	84.5	0.5	65	150
DC-210	210	231	230	50	447.3	1500	85	86.5	0.5	65	150
DC-215	215	236.5	230	50	457.8	1500	85	88.5	0.5	65	150
DC-220	220	242	230	50	468.3	1500	85	90.5	0.5	65	150
DC-225	225	247.5	230	50	478.8	1500	85	92.5	0.5	65	150
DC-230	230	253	230	50	489.3	1500	85	94.5	0.5	65	150
DC-235	235	258.5	230	50	499.8	1500	85	96.5	0.5	65	150
DC-240	240	264	230	50	510.3	1500	85	98.5	0.5	65	150
DC-245	245	269.5	230	50	520.8	1500	85	100.5	0.5	65	150
DC-250	250	275	230	50	531.3	1500	85	102.5	0.5	65	150
DC-255	255	280.5	230	50	541.8	1500	85	104.5	0.5	65	150
DC-260	260	286	230	50	552.3	1500	85	106.5	0.5	65	150
DC-265	265	291.5	230	50	562.8	1500	85	108.5	0.5	65	150
DC-270	270	297	230	50	573.3	1500	85	110.5	0.5	65	150
DC-275	275	302.5	230	50	583.8	1500	85	112.5	0.5	65	150
DC-280	280	308	230	50	594.3	1500	85	114.5	0.5	65	150
DC-285	285	313.5	230	50	604.8	1500	85	116.5	0.5	65	150
DC-290	290	319	230	50	615.3	1500	85	118.5	0.5	65	150
DC-295	295	324.5	230	50	625.8	1500	85	120.5	0.5	65	150
DC-300	300	330	230	50	636.3	1500	85	122.5	0.5	65	150
DC-305	305	335.5	230	50	646.8	1500	85	124.5	0.5	65	150
DC-310	310	341	230	50	657.3	1500	85	126.5	0.5	65	150
DC-315	315	346.5	230	50	667.8	1500	85	128.5	0.5	65	150
DC-320	320	352	230	50	678.3	1500	85	130.5	0.5	65	150
DC-325	325	357.5	230	50	688.8	1500	85	132.5	0.5	65	150
DC-330	330	363	230	50	699.3	1500	85	134.5	0.5	65	150
DC-335	335	368.5	230	50	709.8	1500	85	136.5	0.5	65	150
DC-340	340	374	230	50	720.3	1500	85	138.5	0.5	65	150
DC-345	345	379.5	230	50	730.8	1500	85	140.5	0.5	65	150
DC-350	350	385	230	50	741.3	1500	85	142.5	0.5	65	150
DC-355	355	390.5	230	50	751.8	1500	85	144.5	0.5	65	150
DC-360	360	396	230	50	762.3	1500	85	146.5	0.5	65	150
DC-365	365	401.5	230	50	772.8	1500	85	148.5	0.5	65	150
DC-370	370	407	230	50	783.3	1500	85	150.5	0.5	65	150
DC-375	375	412.5	230	50	793.8	1500	85	152.5	0.5	65	150
DC-380	380	418	230	50	804.3	1500	85	154.5	0.5	65	150
DC-385	385	423.5	230	50	814.8	1500	85	156.5	0.5	65	150
DC-390	390	429	230	50	825.3	1500	85	158.5	0.5	65	150
DC-395	395	434.5	230	50	835.8	1500	85	160.5	0.5	65	150
DC-400	400	440	230	50	846.3	1500	85	162.5	0.5	65	150
DC-405	405	445.5	230	50	856.8	1500	85	164.5	0.5	65	150
DC-410	410	451	230	50	867.3	1500	85	166.5	0.5	65	150
DC-415	415	456.5	230	50	877.8	1500	85	168.5	0.5	65	150
DC-420	420	462	230	50	888.3	1500	85	170.5	0.5	65	150
DC-425	425	467.5	230	50	898.8	1500	85	172.5	0.5	65	150
DC-430	430	473	230	50	909.3	1500	85	174.5	0.5	65	150
DC-435	435	478.5	230	50	919.8	1500	85	176.5	0.5	65	150
DC-440	440	484	230	50	930.3	1500	85	178.5	0.5	65	150
DC-445	445	489.5	230	50	940.8	1500	85	180.5	0.5	65	150
DC-450	450	495	230	50	951.3	1500	85	182.5	0.5	65	150
DC-455	455	500.5	230	50	961.8	1500	85	184.5	0.5	65	150
DC-460	460	506	230	50	972.3	1500	85	186.5	0.5	65	150
DC-465	465	511.5	230	50	982.8	1500	85	188.5	0.5	65	150
DC-470	470	517	230	50	993.3	1500	85	190.5	0.5	65	150
DC-475	475	522.5	230	50	1003.8	1500	85	192.5	0.5	65	150
DC-480	480	528	230	50	1014.3	1500	85	194.5	0.5	65	150
DC-485	485	533.5	230	50	1024.8	1500	85	196.5	0.5	65	150
DC-490	490	539	230	50	1035.3	1500	85	198.5	0.5	65	150
DC-495	495	544.5	230	50	1045.8	1500	85	200.5	0.5	65	150
DC-500	500	550	230	50	1056.3	1500	85	202.5	0.5	65	150

. Why Choose Us:

Dedicated
We are DEDICATED to meet Customers' need.

Enthusiasm
We respond to our Customers' ENTHUSIASM

Loyalty
We cherish our Customers' LOYALTY

Luxury
We aim to establish our own LUXURY brand

Efficient
We offer our EFFICIENT service

Newest
We adopt NEWEST technologies for products

Trust
We strive for winning the TRUST from Customers

. QUALIFICATION CERTIFICATE:



. FACTORY INTERIOR:



FAQ

Q: What's your delivery time?

A: Standard product 20 days - 30 days.

Q: Can we add our logo to products?

A: Yes, there are several ways to do this. We can put the label of your logo on the products or make the silk print of your logo on the products. It is free.

Q: Can we customize the product?

A: We have a very experienced technical team, we can customize any product according to your requirements, such as synchronization system, wet exhaust system, ultra-silent system



Fuan Dellent Electric & Machinery Co., Ltd.

+8613706938606

jennifer@dellent.com

dellentpower.com

NO.7,JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN
CITY,NINGDE CITY,FUJIAN,CHINA